

ZLOG-T

Multi-Use Temperature Data Logger



Technical Specifications

Battery life	Up to 2 years (1 year storage / 1 year useful life) @25°C, 5 minutes logging interval
Operation Temperature	-30°C~70°C
Measurement Accuracy	±0.5°C, @-10~40°C, ±0.8°C@-30~-10°C & 40~70°C
Resolution	0.1°C
Alarm Limit	Up to 6 individually programmable alarm limits
Logging Interval	1 minute -24 hours optional (Default 10 minutes)
Memory Space	Up to 33,000 points@Single PDF/CSV report, 25,000 Points @PDF&CSV report
Start Delay	0 minute -24 hours optional (Default 15 minutes)
Start Mode	Manual/Auto start
Report Format	PDF/CSV/PDF&CSV(optional)
IP Grade	IP65
Battery Type	3.0V CR2450
Connection	USB2.0
Weight	35.6g
Dimensions	102.5*40*13.5mm
Certification	CE, EN12830:2018, RoHS

Smart Analyzing

Built-in intelligent data analysis automatically identifies temperature anomalies and generates actionable insights.

Online Configuration

Configure parameters remotely via cloud platform - no on-site setup or local operation required

Complies with EN12830

Fully conforms to EN12830 standard - ensures standardized and reliable temperature monitoring.

Non-Drive Report

Plug-and-play report generation - no additional driver or software installation needed.

LED Indication

Intuitive LED status indicators - delivers clear visual feedback of working status at a glance

About Us

Shams Free Zone, Al Messaned, Al Bataeh, Sharjah, UAE, PO Box:66636
contact No: +971 54 370 4505
Email: sales@nuatekglobal.com